



Product description

HAHN Louvre Window „Type naco“

System construction and characteristics:

- Certified according and DIN EN 14351-1
- TÜV certified compliance test according EC machinery directive 2006/42/EG
- Filigree glass fixing clips
- Overlapping louvre blades, fixed to short sides only
- Louvre height 152 mm
- Frame depth 46 mm, Frame facing 13 mm top and bottom, 33.5 mm side

Installation:

- Window frame suitable for screw fixing into brickwork, timber- and steel constructions
- Glazing flange for facade systems, details depending on building situation

Glazing:

- Single glazing (glass thickness 6 mm)
- Glass types: Float glass, toughened glass, figured glass; Timber, aluminum (ellipsoid or finned) and/or plastic panels alternatively (depending on statically requirements)

Control types:

- Manually by Hand lever (with linkage where necessary), crank gear controls, electrically by different 24V/230V actuators, pneumatic control

Material and surface:

- Frame surface either anodised 20 micron silver (special colours on request)
- ppc finish in RAL, DB or special colours on request, surface of side fixing frame laquer coated in RAL, DB or special colours

Detail description:

Louvre Window System:	Type naco
Frame Width x Height:	_____ x _____ (Outer frame dimensions)
Glazing flange, size:	_____ x _____
Number of louvres:	_____
Installation details:	_____
Glazing:	_____
Control:	_____
Surface:	_____

Manufactured by

HAHN Lamellenfenster GmbH

Hafenstrasse 5

63811 Stockstadt

info@hahn-lamellenfenster.de

<http://www.hahn-lamellenfenster.de>