

Product description

HAHN Louvre Window "Type NACO"

System construction and characteristics:

- Filigree glass fixing clips
- Overlapping louvre blades, fixed to short sides only
- Louvre height 152 mm
- Frame depth 46 mm, Frame facing 13 mm top and bottom, 33.5 mm side,

Installation:

- Window frame suitable for screw fixing into brickwork, timber- and steel constructions
- Glazing flange for facade systems, details depending on building situation

Glazing:

- Single glazing (glass thickness 6 mm)
- Glass types: Float glass, toughened glass, figured glass. Timber, aluminium (ellipsoid or finned) and/or plastic panels alternatively (depending on statically requirements)

Control types:

- Manually by Hand lever (with linkage where necessary), crank gear controls, electrically by different 24V/230V actuators, pneumatic control

Material and surface:

- Frame surface either anodised 20 micron silver (special colours on request) or with ppc finish in RAL, DB or special colours on request, surface of side fixing frame laquer coated in RAL, DB or special colours

Detail description:

Louvre Window Frame Width x Glazing flange, Number of louv Installation det Glazing: Control: Surface:	Height: size: vres:	Type NACOXX	_ (Outer frame dimensions)
Manufactured by	nufactured by HAHN Lamellenfenster GmbH Hafenstrasse 5 63811 Stockstadt		

info@hahn-lamellenfenster.de http://www.hahn-lamellenfenster.de