



## Product description

### **HAHN Louvre Window „Type S9-45“**

#### System construction and characteristics:

- Made from thermal broken aluminium profiles
- Flush glazed
- No overlapping louvre blades due to 45° polished top and bottom glass edges
- Louvre blades point fixed
- Frame depth 47 mm, Frame facing 18 mm top and bottom, 50 mm side,

#### Installation:

- Window frame suitable for screw fixing into brickwork, timber- and steel constructions
- Glazing flange for facade systems, details depending on building situation

#### Glazing:

- Single glazing (glass thickness 8,10 or 12 mm) standard toughened glass
- Glass types: Special glass depending on purpose of windows. Timber, aluminium and/or plastic panels alternatively (depending on statically requirements)

#### Control types:

- Manually by Hand lever (with linkage where necessary), crank gear controls, electrically by different 24V/230V actuators, pneumatic control

#### Material and surface:

- Surface either anodised 20 micron silver (special colours on request) or with ppc finish in RAL, DB or special colours (dual colour coat is also available), on request

#### Detail description:

Louvre Window System:	Type S9-45
Frame Width x Height:	_____ x _____ (Outer frame dimensions)
Glazing flange, size:	_____ x _____
Number of louvres:	_____
Installation details:	_____
Glazing:	_____
Control:	_____
Surface:	_____

Manufactured by HAHN Lamellenfenster GmbH  
Hafenstrasse 5  
63811 Stockstadt  
[info@hahn-lamellenfenster.de](mailto:info@hahn-lamellenfenster.de)  
<http://www.hahn-lamellenfenster.de>