



Product description

HAHN Louvre Window „Type S9-45“

System construction and characteristics:

- Certified according DIN EN 14351-1
- TÜV certified compliance test according EC machinery directive 2006/42/EG
- Water tightness classification 1A
- Wind load resistance classification C2
- Air permeability class 2
- Made from thermal broken aluminum profiles
- Flush glazed
- No overlapping louvre blades due to 45° polished top and bottom glass edges
- Louvre blades point fixed
- Frame depth 47 mm; Frame facing 18 mm top and bottom, 50 mm side

Installation:

- Window frame suitable for screw fixing into brickwork, timber- and steel constructions
- Fixation by fastening tab
- Glazing flange for facade systems, details depending on building situation

Glazing:

- Single glazing (glass thickness 8, 10 or 12 mm) standard toughened glass
- Glass types: Special glass depending on purpose of windows; Timber, aluminum and/or plastic panels alternatively (depending on statically requirements)

Control types:

- Manually by Hand lever (with linkage where necessary), crank gear controls, electrically by different 24V/230V actuators, pneumatic control

Material and surface:

- Surface either anodised 20 micron silver (special colours on request)
- ppc finish in RAL, DB or special colours (dual colour coat is also available)

Detail description:

Louvre Window System: Type S9-45
Frame Width x Height: _____ x _____ (Outer frame dimensions)
Glazing flange, size: _____ x _____
Number of louvres: _____
Installation details: _____
Glazing: _____
Control: _____
Surface: _____

Manufactured by

HAHN Lamellenfenster GmbH
Hafenstrasse 5
63811 Stockstadt

info@hahn-lamellenfenster.de

<http://www.hahn-lamellenfenster.de>