



Product description

HAHN Louvre Window „Type Integral“

System construction and characteristics:

- Certified according DIN EN 12101-2 for smoke and heat-ventilation
- TÜV certified compliance test according EC machinery directive 2006/42/EG
- Made from thermal broken aluminium profiles
- Actuator invisible hidden into window frame
- Louvre windows flush with outer frame
- Framed controllable double glazed louvres
- Optionally: Ball impact safety
- Frame depth 80 mm, Frame facing 20 mm top and bottom, 48 mm side,
Total thickness vent sash: 35 mm

Installation:

- Window frame suitable for screw fixing into brickwork, timber- and steel constructions
- Glazing flange for facade systems, details depending on building situation

Glazing:

- Double- or triple glazing (Glass thickness 28 mm, standard glazing 6/16/6)
- Glass types: Heat insulation glass, Solar glass, Special glass like safety glass etc. depending on purpose of windows. Insulated panels in lieu of glass alternatively.

Control types:

- 24V Actuator, alternatively manually with hand lever

Material and surface:

- Surface either anodised 20 micron silver (special colours on request)
or with ppc finish in RAL, DB or special colours (dual colour coat is also available), on request

Detail description:

Louvre Window System:	Type Integral
Frame Width x Height:	_____ x _____ (Outer frame dimensions)
Glazing flange, size:	_____ x _____
Number of louvres:	_____
Installation details:	_____
Glazing:	_____
Control:	_____
Surface:	_____

Manufactured by HAHN Lamellenfenster GmbH
Hafenstrasse 5
63811 Stockstadt
info@hahn-lamellenfenster.de
<http://www.hahn-lamellenfenster.de>