



Product description

HAHN Louvre Window „Type S9“

System construction and characteristics:

- Certified according DIN EN 12101-2 for smoke and heat-ventilation
- TÜV certified compliance test according EC machinery directive 2006/42/EG
- Made from non thermal broken aluminium profiles
- Overlapping louvre blades, fixed to short sides only
- Louvre size and overlapping variable
- Frame depth 46 mm, Frame facing 13 mm top and bottom, 48 mm side,

Installation:

- Window frame suitable for screw fixing into brickwork, timber- and steel constructions
- Glazing flange for facade systems, details depending on building situation

Glazing:

- Single glazing (glass thickness 8,10 or 12 mm)
- Glass types: Special glass depending on purpose of windows. Timber, aluminium and/or plastic panels alternatively (depending on statically requirements)

Control types:

- Manually by Hand lever (with linkage where necessary), crank gear controls, electrically by different 24V/230V actuators, pneumatic control

Material and surface:

- Surface either anodised 20 micron silver (special colours on request) or with ppc finish in RAL, DB or special colours on request

Detail description:

Louvre Window System:	Type S9
Frame Width x Height:	_____ x _____ (Outer frame dimensions)
Glazing flange, size:	_____ x _____
Number of louvres:	_____
Installation details:	_____
Glazing:	_____
Control:	_____
Surface:	_____

Manufactured by HAHN Lamellenfenster GmbH
Hafenstrasse 5
63811 Stockstadt
info@hahn-lamellenfenster.de
<http://www.hahn-lamellenfenster.de>