



## Product description

### **GLASBAU HAHN Louvre Window „Type S9-iVt-05 Allglass“**

#### System construction and characteristics:

- Certified according DIN EN 12101-2 for smoke and heat-ventilation
- TÜV certified compliance test according EC machinery directive 2006/42/EG
- Made from thermal broken aluminium profiles
- Flush glazed
- Optionally: Ball impact safety
- Frame depth 47/50 mm, Frame facing 18 mm top and bottom, 50 mm side,  
Total thickness vent sash: 41 mm

#### Installation:

- Window frame suitable for screw fixing into brickwork, timber- and steel constructions
- Glazing flange for facade systems, details depending on building situation

#### Glazing:

- Double- or triple glazing (Glass thickness 32/34 mm, standard glazing 4/22/6 or 6/20/8)
- Glass types: Heat insulation glass, Solar glass, Special glass like safety glass etc. depending on purpose of windows. Insulated panels in lieu of glass alternatively.

#### Control types:

- Manually by Hand lever (with linkage where necessary), crank gear controls,  
electrically by different 24V/230V actuators, pneumatic control

#### Material and surface:

- Surface either anodised 20 micron silver (special colours on request)  
or with ppc finish in RAL, DB or special colours (dual colour coat is also available), on request

#### Detail description:

Louvre Window System:	Type S9-iVt-05 Allglass
Frame Width x Height:	_____ x _____ (Outer frame dimensions)
Glazing flange, size:	_____ x _____
Number of louvres:	_____
Installation details:	_____
Glazing:	_____
Control:	_____
Surface:	_____

Manufactured by      Glasbau Hahn GmbH  
                                  Hafenstrasse 5  
                                  63811 Stockstadt  
                                  [info@glasbau-hahn.de](mailto:info@glasbau-hahn.de)  
                                  <http://www.glasbau-hahn.de>